



BenQ DC C540

Version: 01-Aug-2006



Product Features

5 megapixels CCD / 3X optical zoom

Large 2.5" LTPS screen

smc Pentax lens (Super Multi-Coating)

PASM mode

Provide **A**perture (decide the depth of field), **S**hutter(decide exposure time), **M**anual(users adjust aperture and shutter), and **P**rogram(automatically decide between aperture and shutter according to the environment) modes to satisfy even the photo expertise.

Shake-Free mode

High ISO portrait mode

Support high sensitivity (ISO) to light **up to 800** to ensure clear photos in dark environment.

3:2 and 16:9 special output size

- 3:2 resolution mode supported for easy printing without trimming edges.
- 16:9 resolution mode supported for direct display on 16:9 TV.

13 scene modes

Program / Sunset / Backlight / Landscape / High ISO Portrait / Snow / Fireworks / Night Scene / Kids / Food / Building / Shake-Free / Text

Continuous Shooting till memory full

Direct printing mode supported

PictBridge compatible

Multi-Metering

Easy for you to capture well-exposed photos when there exist many bright and dark objects in the scene.

Continuous movie recording with Optical Zoom

Specifications

Image Sensor	5.0 Mega Pixels CCD, Size: 1/2.5 inch
Image Resolution	2560 x 1920 (5M) / 2560 x 1712 (3:2) / 2560 x 1440 (16:9) / 2048 x 1536 (3M) / 1024 x 768 (1M) / 640 x 480 (VGA)
Lens	smc Pentax lens f = 6.2 (W) ~ 18.6 (T) mm, (35mm film equivalent: 37.5 ~112.5mm); F/2.8 (W) ~ 5.2 (T)
Zoom	Optical: 3X Digital: 4X
LCD	2.5" LTPS LCD / 150K Dot
Dimensions / Weight	91.5 x 61.5 x 26 (32 slimmest) mm / 140 g (without battery & SD card)
Power Source	AA Battery x 2
Storage Type	Built-in 9 MB SD card compatible
Focus Range	Normal: 80cm ~ Infinity Macro: 15cm ~ 1m
Shutter Speed	1/2000 ~ 8 sec
Movie Mode	Video: 640 x 480 / 320 x 240 / 160 x 120 (30fps) Continuous recording with sound
White Balance	Auto / Daylight / Cloudy / Tungsten / Fluorescent (H) / Fluorescent (L) / MWB
Exposure	-2~+2 EV (0.3EV / step)
ISO	Auto / 50 / 100 / 200 / 400
Flash	Auto / Red eye reduction / Forced on / Slow sync / Forced off
Self-Timer	2 sec./ 10 sec./ 10+2 sec
File Format	Still Image: JPEG (EXIF 2.2 compatible), DCF compatible, Support DPOF Video: M_JPEG / Audio: WAV
Interface	Digital output: USB 2.0 Audio / Video output (NTSC/PAL) Pictbridge
Accessory	- USB cable - Software CD ROM - User's Manual - Hand Strap - Pouch - AV Cable - AA battery x 2